

BoscoLighting's thin low bay light is tough- built for places it might get shaken, beaten or exposed to the elements. This low bay fitting includes flex&plug and chain, so installation could not be easier. It can also be mounted as a fixture to ceilings or walls.

As with most of our product range, our low bays are interconnectable with our intelligent lighting control system and can be turned on and off again without any warm up or cool down restrictions. With special heat management design, this light is designed to operate 24/7 for up to 3 years without missing a beat!

Features

- Maintenance free and quality build to protect against vibrations and ensure long lasting life
- Electrician friendly - Easy to install
- LED Driver Included
- Supplied with Flex & Plug
- An IP65 rating ensure that these lights are waterproof and suitable for indoor or outdoor use

Applications

- Loft-style offices
- Sporting locations including gymnasiums, indoor sporting halls and community centres
- Industrial factories, workshops and warehouses
- Supermarkets and exhibition centers


High Bay UFO1




Specs

Connect: AU Standard Flex & Plug

Dimming: Various dimming options available on request



| ← D → |
(Top View)



| ← H → |
(Side View)



BLBL-UFO1-60

60W Bay Light
Luminous Flux (lm): 7200
CCT: Whites(3000K-6500K)
Dimensions (mm): D230*H180
Weight(kg): 2.3




BLBL-UFO1-80

80W Bay Light
Luminous Flux (lm): 8000
CCT: Whites(3000K-6500K)
Dimensions (mm):D230*H180
Weight(kg): 3



BLBL-UFO1-150

150W Bay Light
Luminous Flux (lm): 16500
CCT: Whites(3000K-6500K)
Dimensions (mm): D350*H275
Weight(kg): 5.7



BLBL-UFO1-200

200W Bay Light
Luminous Flux (lm): 22000
CCT: Whites(3000K-6500K)
Dimensions (mm): D350*275
Weight(kg): 5.9



BLBL-UFO1-240

240W Bay Light
Luminous Flux (lm): 27500
CCT: Whites(3000K-6500K)
Dimensions (mm): D450*H290
Weight(kg): 9