

BLEX-TL006

BLEX-TL006 is a streamlined Plaster-in Trimless Extrusion for ceiling or wall recessed. At 18.5 mm deep with a light emitting surface of approx 10 mm, the profile is designed to deliver a narrow lighting effect.

Supplied as standard in 2m lengths. The extrusion can be recessed easily into walls or ceilings using a thin layer of plaster. We offer cut-to-length service as well. (MOQ may apply)

It can be fitted with one BoscoLighting SMD2835, SMD5050, SMD3528 or other LED strip for interior lighting.

*LEDs and driver not included.

Features

- Easy to cut to size or extend as needed
- Good heatsinking for LED longevity
- Default fitting colour: anodised silver

Accessories

- 2 Poly End Caps per standard length
- Diffuser - Frosted
- Optional Joiner on request

Product Specifications

Dimensions (mm): 1000*53*18.5

Cut-out(mm): 1000*15*16

Installation Instruction

- Step 1: Fix the trimless extrusion in minimum 16mm Plasterboard or Gyprock using metal screws to hold it in position or using plasterboard or drywall adhesives. Or make a cut-out into the ceiling or wall as per the required cut-out dimension, then fix the trimless extrusion in position.
- Step 2: Once done, patch over the mounting frame with stucco or plaster and paint and let it dry to finish then install strip and diffuser.

Plaster-in Trimless Extrusion TL006

