

## BLEX-TL021

Introducing BLEX-TL021 Plaster-in Ceiling Shadow Gap Profile, the ultimate solution for seamless wall-to-ceiling junctions. This innovative trim elevates the transition between the wall and ceiling, transforming it into a captivating focal point.

Combining practicality with aesthetics, BLEX-TL021 is the ideal choice for modern homes and commercial spaces.

Supplied in 2-meter lengths as standard, the high-quality aluminum extrusion can be easily tailored to your specifications. Experience the perfect blend of functionality and style with BLEX-TL021, making every interior space a truly remarkable masterpiece. (MOQ may apply).

### Features

- Easy to cut to size or extend as needed
- Good heatsinking for LED longevity
- Default fitting colour: anodised silver

### Accessories

- 2 Poly End Caps per standard length
- Diffuser - Frosted
- Optional Joiner on request

### Product Specifications

Dimensions (mm): 1000\*38.2\*15

### Installation Instruction

- Step 1: Before fixing or putting the extrusion in place, make sure all LED strips or any required electrical cables had been installed already inside the extrusion. Otherwise, it may be quite difficult to place these LED strips and electrical cables inside the extrusion once it is already in place.
- Step 2: Fix the trimless extrusion in Plasterboard/Gyprock using metal screws to hold it in position or using plasterboard or drywall adhesives.
- Step 3: Once done, patch over the mounting frame with stucco or plaster and paint and let it dry to finish then install strip and diffuser.

## Plaster-in Trimless Extrusion TL021

