



BoscoLighting's TEX Linear Pendant Light System is a combination of Tetris anti-glare spotlight and diffused extrusion lighting.

Bold and subtle at the same time, **TEX** is a great way to light up your projects in decorative and practical ways.

Sleek linear profile produces low glare lighting. It is a product that creates an eye-catching statement and inspirational lighting schemes for architectural and commercial projects.

Pendant Light TEX



Applications

- Museums & galleries
- Retail shops
- Libraries
- Residential and commercial projects

Features



- It comes with standard 1.2m lengths, also available at 1.5m on request.
- Straight line joiner and corner joiner available for continuous lines
- Inbuilt constant current power supply(for non-dim)
- Optional dimming on request: Trailing edge dimming or DALI dimming control
- Anodised silver as standard fitting colour. Can be customised in a powder coated white or black finish.(MOQ may apply)



BLPD-TEX1-12

50W Low Glare Pendant Light

Power (W): 50
Luminous Flux (lm): 2950
Connect: AU Standard Flex & Plug
CCT: 3000K-6500K
CRI: >80 (default) or 92
Viewing Angle: 15/30/45
Dimming: Non-dim, Trailing edge, DALI
IP Rating: 40
Dimensions (mm): L1200*W54*H84
Weight (kg): 2.5



BLPD-TEX2-12

47W Low Glare Pendant Light

Power (W): 47
Luminous Flux (lm): 3185
Connect: AU Standard Flex & Plug
CCT: 3000K-6500K
CRI: >80 (default) or 92
Viewing Angle: 15/30/45
Dimming: Non-dim, Trailing edge, DALI
IP Rating: 40
Dimensions (mm): L1200*W54*H84
Weight (kg): 2.5



BLPD-TEX3-12

30W Low Glare Pendant Light

Power (W): 30
Luminous Flux (lm): 1755
Connect: AU Standard Flex & Plug
CCT: 3000K-6500K
CRI: >80 (default) or 92
Viewing Angle: 15/30/45
Dimming: Non-dim, Trailing edge, DALI
IP Rating: 40
Dimensions (mm): L1200*W54*H84
Weight (kg): 2.5

