

Revolutionise your lighting solutions with our IP65 SMD5050 RGBW Strip Light, now available in convenient 5-meter rolls.

Although RGB can produce colours close to Whites, a dedicated RGBW LED chip can provide a much purer white tone (optional in 3000K, 4000K, 6000K) and allows you to create a massive range of unique shades.

Offering enhanced flexibility and versatility, it excels in wet areas like kitchens, bathrooms, and outdoor spaces.

## **Features**

- Enhanced Flexibility: SMD5050 RGBW offers superior flexibility for seamless integration into various spaces, adhering to surfaces effortlessly.\*
- Waterproof Design: IP65 rating ensures resistance to water and dust, ideal for indoor and outdoor use.
- DMX Compatibility: Control with precision using DMX input, compatible with 12/24V DC power supplies and RGBW DMX
- **Extended Lifespan:** Over 70 type of aluminium extrusions including flush and surface mounted as well as suspension options for housing the strips. These extrusions provide protection and a polished finish suitable for visible installations.
- Optional Pre-Assembled Service: Opt for our optional preassembled service (available when ordering LED extrusions and LED drivers) to streamline your installation, guaranteeing a seamless and professional finish with ease.
- Customised Lengths: Available in standard 5-meter rolls. For tailored requirements, please allow for a longer lead time.

\*Wipe dry the extrusion using a lint-free cloth before installation, peel back the tape backing and stuck in place using a static glove. Correct installation of this product requires a few dabs of silicon along the length to hold it in place. The glue is normally enough, but sometimes it doesn't stick so well to the paint and so we recommend a little dab of silicon every 20cm or so on each side of strip in a zig-zag pattern.

## **Product Code** BLSP-5050-60-WP-RGBW Power (W) 14.4W/m (max.) Luminous FLux(Im) 1224lm/m (max.) RGB & Warm White (3000K); RGB & Neutural CCT White (4000K); RGB & Cool White (6000K) **IP65** IP Rating Insulated Cable Connect Various dimming options available on request **Dimming Options** 12\*1000 Dimensions(mm) 0.1 Weight(kg)

## **RGBW Strip Light** SMD5050 **IP65**


























5.0mm